



DECKING OIL

DESCRIPTION

“Kingfisher Decking Oil” is a solvent-borne protective treatment formulated primarily for timber decking but which can also be used on a variety of exterior timbers. It is a non-film forming treatment which allows the timber to breathe while still providing excellent protection against weathering.

BENEFITS

- For the treatment of timber decking, cladding and end grain.
- Protects against wood rotting fungi and wood boring insects.
- Protects against weathering.
- Rejuvenates faded decking boards and cladding.

AREAS OF USE

“Kingfisher Decking Oil” can be used on most types of timber decking and for treating end grain.

Note: Areas of “heavy traffic” may require annual re-application.

APPLICATION

“Kingfisher Decking Oil” is supplied “ready to use” Shake well before use and apply two coats by brush, spray or dipping. Apply the second coat has been fully absorbed but ideally before it has dried completely. Apply only to dry surfaces and with no rain expected for at least 5 hours after application.

- Always test an inconspicuous area or off cut of timber prior to full application.
- Avoid contact with bitumen, roofing felt and plastics.
- It is the user’s responsibility to determine suitability for use.
- If in doubt contact Kingfisher Technical Services Department for advice

SURFACE PREPARATION

Check new decking for absorption as some boards are waxed at time of manufacture and may not readily absorb the “Kingfisher Decking Oil”.

Older decking should be cleaned by either pressure washing or scrubbing; but in the case of pressure washing, care should be taken not to raise or damage the grain.

All existing paints or finishes should be removed back to bare sound timber prior to treatment and any rotten boards replaced.

COVERAGE

Apply 2-3 coats at a rate of 1 litre of product per 4-5m² of surface. Dip end grains for a minimum of 10 minutes.

STORAGE

Keep away from food. Store in unopened containers in cool, dry conditions away from sources of ignition and heat.

PACKAGING /SHELF LIFE

“Kingfisher Decking Oil” is available in 5 litre packs. Shelf life is two years when stored as recommended.

HEALTH AND SAFETY

Avoid eye contact and wear suitable protective gloves.

For further Health and Safety information on this product please refer to the Kingfisher Safety Data Sheet, copies of which are available from the Kingfisher Technical Dept. Tel. 01229 869100 or Fax 01229 868101.

THE INFORMATION GIVEN IN THIS DATA SHEET RELATES ONLY TO THE SPECIFIC MATERIAL DESIGNATED AND MAY NOT BE VALID FOR SUCH MATERIAL USED IN COMBINATION WITH ANY OTHER MATERIALS OR IN ANY PROCESS. SUCH INFORMATION IS TO THE BEST OF THE COMPANY'S KNOWLEDGE AND BELIEF, ACCURATE AND RELIABLE AS OF THE DATE INDICATED.

HOWEVER NO WARRANTY, GUARANTEE OR REPRESENTATION IS MADE AS TO ITS ACCURACY, RELIABILITY OR COMPLETENESS. IT IS THE USER'S RESPONSIBILITY TO SATISFY THEMSELVES AS TO THE SUITABILITY AND APPLICATION OF SUCH INFORMATION FOR THEIR OWN USE.