



ECOBOR 20 WOOD PRESERVATIVE & SURFACE BIOCIDES GEL

Ecobor 20 is a special boron-based and Benzalkonium chloride brushable and injectable gel. For use in high risk areas to treat against dry and wet rot as well as algae, mould fungi and wood destroying insects.

Ecobor 20 has been designed for use on all timbers at high risk of damage or decay such as joist ends, purlins, wall plates, cut ends and rafter ends.

Ecobor 20 leaves no surface residues after treatment, is non-staining and can be overpainted in time.

- Brushable and injectable multi-use gel
- Excellent highly penetrating preservative for the control of wood - rotting fungi and wood boring insects
- Approved under COPR 1986 for use as a wood preservative and surface biocide
20% Disodium octaborate tetrahydrate as the active ingredient with Benzalkonium chloride
- Clean, easy to handle and virtually non-drip
- A clear and non-staining preservative gel
- Odourless and non-flammable
- Permanent protection because the active ingredient does not break down

DIRECTIONS FOR USE

Treatment of wood boring insects and fungal decay in timber:

1. Clean all wooden surfaces using a brush or vacuum cleaner.
2. To aid brushing out on any timbers, which are very dry or remain dusty, spray or brush a little water to the surface before the application of **ACS Ecobor 20**.
3. Apply a generous brush coat of **ACS Ecobor 20**, taking care to ensure that end grains, corners and joints are well treated. Brush apply to any surfaces exposed by cutting after initial treatment.
4. Brush the **ACS Ecobor 20** well into the surface taking care not overload the brush with the product, particularly on overhead, horizontal faces.
5. **ACS Ecobor 20** may be used in outdoor conditions provided that the timber treated is then protected from weathering by an appropriate coating or sealant.

6. As a surface application the gel will not penetrate through paint, varnishes or other coatings and these should be removed before treatment. **ACS Ecobor 20** can be injected through predrilled holes in areas where paint and coatings cannot be removed.
7. Clean all tools, brushes and equipment with water.

For masonry sterilization (dry rot, algae and mould fungi)

1. Clean down surface to remove any loose or flaking material and loose organic growth.
2. Apply one liberal coat of **ACS Ecobor 20** and allow the product to penetrate the masonry.
3. If treating dry rot outbreaks, apply **ACS Ecobor 20** to the reverse face any new timber, such as skirting and architrave before fixing.

COVERAGE

By brush : 1 litre to 2 - 2.5 m² of timber surface
Large dimensional timbers may need more than one coat or additional treatment with Ecobor 40 Paste.

By injection : Apply as necessary or until refusal through predrilled holes.

PACKAGING

Available in 310ml and 400ml cartridge, 2.5 and 5 litre robust plastic containers.

SHELF LIFE AND STORAGE

At least twelve months in unopened, sealed containers.

Store in original packaging, unopened or sealed in a dry, safe place.

Keep out of reach of children.

Keep away from food, drink and animal feedstuffs.

Viscosity may be reduced at elevated temperatures.

HEALTH AND SAFETY

ACS Ecobor II is approved under the HSE COPR 1986 for use as directed HSE No: 10584. Refer to Safety Data Sheet (SDS) for the product. Use only as a wood preservative. Keep away from children and always read the label.

Information given is in good faith based on experience and usage, however all recommendations are made without warranty or guarantee, since the conditions of use are beyond our control. All goods are sold in accordance with our Conditions of Sale, copies of which are available on request. Customers are advised that products, techniques and codes of practice are under constant review and changes occur without notice, please ensure you have the latest updated information.

Advanced Chemical Specialties Limited
9, Bofors Park, Artillery Road,
Yeovil, Somerset BA22 8YH
UK

☎ 01935 414012

info@acslimited.co.uk

www.acslimited.co.uk

November 2018