

INTERIOR BRICK & DUST SEALER

Appearance	Matt finish
Coverage	5 to 6 m ²
Initial cure	2 Hours @ 20 °C
Re-coat	2-4 hours @ 20°C
Full cure	24 hours @ 20°C

DESCRIPTION

Kingfisher “Interior Brick & Dust Sealer” is a very fine particle pure acrylic dispersion (solvent free), formulated to create an excellent penetrating and binding sealer. Being a water based acrylic it is a low odour material, suited to internal applications.

EU limit value for this product (cat.A/h): 30 g/l (2010) This product contains max. 1 g/l VOC.

USES

Seals and enhances:

- Clay Bricks
- Stone (Porous)
- Mortar Joints
- Concrete
- Breeze block (Two coats)

If in doubt, please call Kingfisher Building Products on Technical Dept. Tel: 01229 869 100.

“Anti-Dusting” “Interior Brick & Dust Sealer” is designed to stop troublesome “dusting” typically associated with brick feature walls and decorative interior stone. Older bricks commonly deposit red dust in their vicinity because warm interior conditions dry out the clay surface, encouraging fine particles to lose adhesion and detach. These abrasive particles can damage floors, furniture and even computers. Soft stone and cement or lime mortar joints are similarly problematic. “Interior Brick & Stone Sealer” offers a cost-effective and lasting solution to the problem by binding and sealing porous or friable surfaces with its penetrating clear acrylic ester formula.



Manufacturers to the building industry

Specialist Coatings




Sealants

Roof Coatings



Paving Sealers

Timber Treatments



Damp Proofing

Membranes



Basement Waterproofing

Colour Enhancing “Interior Brick & Dust Sealer” typically darkens the surface very slightly, often enhancing the substrate colour. In most cases one coat is sufficient for dust control but two coats can be applied for enhanced surface protection against liquid staining. Suitable as a feature wall sealer on most mineral based substrates

Protection from staining. Most common building materials (brick/ stone/ mortar / block) are mineral based and are therefore ultimately prone to moisture absorption. Fluids once absorbed into mineral substrates often leave particles behind which “stain” the surface. Two coats of “Interior Brick & Dust Sealer” helps to protect against this problem by sealing the surface to limit absorption.

APPLICATION

In general it is very important that the surface to be treated is dry and any accumulated contaminants are thoroughly cleansed before application. As with all surface treatments you should apply to a small test area to check for compatibility before proceeding to full application. It is the user’s responsibility to establish suitability for the task in hand.

1. Cleaning If the surface to be treated is merely dusty, then vacuum thoroughly until all traces of dust are removed and proceed directly to application. If there is ingrained dirt, wash with clean warm water and only resort to the use of soap detergents if gentle scrubbing with nylon bristle brush and warm water is ineffective. Allow to dry out before proceeding to application
2. Application For a matt “anti-dusting” finish apply 1 coat by brush, roller or low pressure sprayer (not atomizer) on brick and porous stone or masonry joints. A second coat may be applied for a darker or “semi sheen” finish if desired which will also increase protection against liquid staining.

COVERAGE

Dependent on the porosity of the surface 1 litre of product should cover approximately 5 to 6 m²

PACKAGING

Kingfisher Interior Brick & Dust Sealer is supplied in 5 litre & 25 litre Plastic containers. This product is non-flammable. Store in original container in a cool dry place, out of direct sunlight. Do not allow to freeze. Keep out of reach of children.

SHELF LIFE

The product has a shelf life of 12 months from the date of manufacture, subject to correct storage conditions.

Manufacturers to the building industry

Specialist Coatings




Sealants

Roof Coatings



Paving Sealers

Timber Treatments



Damp Proofing

Membranes



Basement Waterproofing

HEALTH & SAFETY

- Wear a face mask and eye protection.
- Wear disposable gloves and overalls during preparation and application.
- Avoid contact with skin and eyes.
- If contact occurs wash immediately with plenty of water. Remove contact lenses if possible.
- Keep out of reach of children.
- Always dispose of empty packaging responsibly.
- Keep children and pets away from treated areas until fully cured.

Before using this product read the Material Safety Data Sheet which can be obtained at www.kingfisheruk.com or by calling the Kingfisher Technical Dept. Tel: 01229 869 100.

The information given in this product data sheet is given in good faith, based on current knowledge and experience. It relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of the company's knowledge and belief, accurate as of the date indicated.