

PATIO BLACK SPOT REMOVER

Appearance	Yellow Translucent finish
Coverage	Approximately 4m ² per litre (use neat) Total max coverage: 5L = 20m ² / 20L = 80m ²



DESCRIPTION

Patio Black Spot Remover is our most powerful cleaning product for patios, pavers & driveways. This product will remove black spot lichens from sandstone, concrete, brick & block pavers. It has a non-acidic formula so can be safely used on limestones and cement-based block pavers. It is highly effective; this product succeeds where pressure washing, and weaker alternatives fail.

USES

The cleaning & prevention of black spot from:

- Natural stones i.e. sandstone
- Porous clay-based & cement-based block pavers
- Concretes
- Brickwork

If in doubt, please call our technical services department on 01229 869 100 for guidance on the many uses for Black Spot Remover.

ADVANTAGES

- Removes black spot where pressure washing fails
- More effective than other cheaper black spot removers due to its unique blend of ingredient
- Use prior to sealing with one of our patio sealers
- Works in conjunction with [Kingfisher Bio-Wash](#) to help prevent the return of black spot

APPLICATION

Carry out a test in an inconspicuous area.

- If you find this product is not suitable for use on your project do not continue to use
- Pre wet the area with clean water, so the surface becomes saturated with water
- Once most of the water is no longer visible on the surface, apply the product
- Apply neat with a sprayer, watering can or direct from the container
- Keep the surface wet by applying more product so it is visibly wet
- Agitate with a stiff brush to prevent the area drying prematurely
- Extend the dwell time for as long as necessary, typically 1 hour+
- Apply in smaller manageable sections when treating large areas
- Do not allow the product to dry on the surface or it ceases to work!

Manufacturers to the building industry

Specialist Coatings



Sealants

Roof Coatings



Paving Sealers

Timber Treatments



Damp Proofing

Membranes



Basement Waterproofing

- Rinse away with plenty of clean water and allow to dry
- Repeat as required.
- Do not exceed the coverage rates
- Do not spray onto adjacent plants & lawns or allow the product to mist over them
- Do not allow this product to enter ponds or encounter aquatic life
- Safe for children, pets & wildlife when dry
- Please allow for some variation in coverage due to the porosity of the surface & level of infestation

IMPORTANT

- This product will not remove bitumen staining
- Only for use for the removal of organic contaminations
- Use this product prior to sealing not after sealing
- Does not prevent the return of black spot

COVERAGE

Approximately 4m² per litre (use neat) Total max coverage: 5L = 20m² / 20L = 80m²

PACKAGING

This product is non-flammable. Store in original container in a cool dry place, out of direct sunlight. Do not allow to freeze. Keep out of reach of children.

SHELF LIFE

This product will lose its strength over time. It is preferable to use the product at the point of purchase or within 6 weeks of this date. The maximum shelf life is 12 months.

HEALTH & SAFETY

- Contact with acids liberates toxic gas
- Harmful if swallowed
- Causes severe skin burns and eye damage
- Very toxic to aquatic life
- Keep out of reach of children
- Do not breathe mist, vapours or spray
- Do not get in eye, on skin, or on clothing
- Wash skin thoroughly after handling
- Avoid release to the environment
- Wear protective gloves/protective clothing/eye protection/face protection

IF SWALLOWED: rinse mouth and do NOT induce vomiting.

IF IN EYES: rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.

Before using this product read the Material Safety Data Sheet which can be obtained at www.kingfisheruk.com or by calling the Kingfisher Technical Dept. Tel: 01229 869 100.

Manufacturers to the building industry

Specialist Coatings




Sealants

Roof Coatings



Paving Sealers

Timber Treatments



Damp Proofing

Membranes



Basement Waterproofing

The information given in this product data sheet is given in good faith, based on current knowledge and experience. It relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of the company's knowledge and belief, accurate as of the date indicated.

All recommendations are made without warranty or guarantee, as to accuracy, reliability, or completeness since the conditions of use are beyond our control. It is the user's responsibility to satisfy themselves as to the suitability and application of such information for their own use.