



KINGFISHER RENDERMIX

DESCRIPTION

Kingfisher RENDERMIX is a highly concentrated additive designed for use to upgrade renders following injected Damp Proof Course operations.

Although Kingfisher RENDERMIX gives water resistant properties to renders, it does not form a vapour barrier and allows drying out without forming damp patches.

Hygroscopic salts are prevented from moving to the surface plaster and exhibiting secondary dampness.

Kingfisher RENDERMIX contains an additive which provides fungal resistance which prevents further outbreaks of fungal growth caused by spores which may remain after removal of the original damp mortar or plaster.

METHOD OF USE

Kingfisher RENDERMIX should be diluted 1 part Rendermix to 40 parts Water BEFORE adding to the mix.

Further specific information on the use of this product can be found in our brochure on DPC operations.

HEALTH & SAFETY

Kingfisher RENDERMIX is supplied as a concentrated viscous alkaline blue liquid. It is water based with a strong alkaline character.

Prolonged contact with skin and splashes to eyes should be avoided.

Store safely; away from children and animals.

For further Health & Safety information on this product please refer to the MSDS, copies of which are available from the Kingfisher Technical Dept. Tel 01229 869100 or Fax 01229 869101

THE INFORMATION GIVEN IN THIS DATA SHEET RELATES ONLY TO THE SPECIFIC MATERIAL DESIGNATED AND MAY NOT BE VALID FOR SUCH MATERIAL USED IN COMBINATION WITH ANY OTHER MATERIALS OR IN ANY PROCESS. SUCH INFORMATION IS TO THE BEST OF THE COMPANY'S KNOWLEDGE AND BELIEF, ACCURATE AND RELIABLE AS OF THE DATE INDICATED.

HOWEVER NO WARRANTY, GUARANTEE OR REPRESENTATION IS MADE AS TO ITS ACCURACY, RELIABILITY OR COMPLETENESS. IT IS THE USER'S RESPONSIBILITY TO SATISFY THEMSELVES AS TO THE SUITABILITY AND APPLICATION OF SUCH INFORMATION FOR THEIR OWN USE.