



KINGFISHER SR20

DESCRIPTION.

Kingfisher SR20 has been specifically developed to remove overspray or spillage of Injection Fluid, Enviroject, Water Repellent, Superseal or Wood Preservatives with Water Repellent. Residue of these products is very difficult to remove, as all water based detergents or cleaners have no effect on the aluminium stearate crystals. SR20 enables quick and effective removal, after which, the area can be rinsed with clean water

METHOD of USE.

Concrete / Stonework : Scrub the affected area with a stiff brush dipped in SR20. Immediately flush with clean water, Repeat procedure until residue is removed.

Glass / Windows : Dampen a dry cloth with SR20 and rub over the affected area. Rinse with clean water.

Paintwork : Dampen a dry cloth with SR20 and test on an unobtrusive area. If paint is unaffected rub onto affected area and flush immediately with clean water.

COVERAGE.

1 litre of SR20 will remove residue from approximately 4 square metres of substrate.

PACKAGING.

1 litre Plastic Container.

HEALTH & SAFETY.

Use only in well ventilated areas. Wear impervious gloves during use. If splashing is likely wear a face visor.

ALWAYS read label before use.

Further Health and Safety information on this product is provided in the MSDS, copies of which are available from the Kingfisher Technical Dept. Tel. 01229 869100 or Fax 01229 869101