



ULTIMATE TOPCOAT

DESCRIPTION

Kingfisher ULTIMATE TOPCOAT is a high grade surface sealer and curing membrane, formulated from acrylic resins and hydrocarbon solvent carrier. It provides a durable, penetrative sealer to a wide variety of surfaces, including concrete, screeds, brickwork, masonry and fibrous sheet materials.

ULTIMATE TOPCOAT is a non degrading system and provides a stable substrate to receive subsequent finishes including epoxy resins, acrylic coatings and cementitious screeds etc.

ADVANTAGES

- Can be applied to green concrete.
- Non-yellowing.
- Dual sealing and curing action.
- High penetration.
- Suitable to receive subsequent treatments.
- Can be used on horizontal or vertical surfaces.

APPLICATION

Preparation: Important! Apply the product to a small discreet area to check compatibility prior to full application.

When used as a sealer/ curing membrane, Ultimate Topcoat should be applied by spray, roller or brush as soon as any surface water has evaporated or immediately on completion of any finishing process.

When used as a surface sealer and dustproofer, all substrates should be clean, sound, and free from contamination and previously applied finishes.

Substrates should be dry to aid penetration but adequate adhesion may be achieved when applied to a damp substrate.

Allow at least two full dry days for treatment surface to be adequately dry before application of ULTIMATE TOPCOAT. (May require more than 48 hours in cold weather conditions.)

Note: Kingfisher Ultimate Topcoat MUST NOT be applied to wet or damp surfaces, if rain is imminent, or if ambient temperatures are below +5°C over a 24 hr period.

Mixing: Supplied ready for use. No mixing required.

Placement: Application may be by brush, roller or spray, applying a complete, even coat to the whole area. A one coat application will provide a slight sheen to the floor and is normally sufficient. However, where further protection is required a further coat may be applied 6-8 hours after the first coat.

COVERAGE

Clear finish with coverage of 4.5 – 7 m² per litre/coat.

PACKAGING

5 litre, 25 litre & 200 litre containers.

TECHNICAL DATA

| | |
|---------------------|------------------|
| S.G. | 0.85 (Clear) |
| Touch Dry. | 2 – 4 hours. |
| Fully Dry. | 24 hours. |
| Dry Film Thickness. | 50 – 90 minutes. |

STORAGE

Store in sealed drums and protect from extreme temperatures.

HEALTH & SAFETY

- Avoid eye and skin contact by use of appropriate protective clothing.
- Use in well ventilated conditions.
- Harmful if ingested.
- Flammable in use.
- Protect from all sources of ignition.

PROTECT FROM FROST
MUST NOT BE APPLIED IN WET

For further Health and Safety information on this product please refer to the Kingfisher Safety Data Sheet, copies of which are available from the Kingfisher Technical Dept. Tel. 01229 869100 or Fax 01229 868101.



THE INFORMATION GIVEN IN THIS DATA SHEET RELATES ONLY TO THE SPECIFIC MATERIAL DESIGNATED AND MAY NOT BE VALID FOR SUCH MATERIAL USED IN COMBINATION WITH ANY OTHER MATERIALS OR IN ANY PROCESS. SUCH INFORMATION IS TO THE BEST OF THE COMPANY'S KNOWLEDGE AND BELIEF, ACCURATE AND RELIABLE AS OF THE DATE INDICATED.

HOWEVER NO WARRANTY, GUARANTEE OR REPRESENTATION IS MADE AS TO ITS ACCURACY, RELIABILITY OR COMPLETENESS. IT IS THE USER'S RESPONSIBILITY TO SATISFY THEMSELVES AS TO THE SUITABILITY AND APPLICATION OF SUCH INFORMATION FOR THEIR OWN USE.