



SAFETY DATA SHEET WOODZONE MASONRY BIOCIDES

Page: 1

Compilation date: 23/01/2015

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: WOODZONE MASONRY BIOCIDES

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: Biokil Crown Ltd

Unit 31 Hilton Industrial Estate

Sutton Lane

Hilton

Derbyshire

DE65 5FE

UK

Tel: +44(0)115 946 0060

Fax: +44(0)115 947 9767

Email: info@biokilcrown.co.uk

1.4. Emergency telephone number

Emergency tel: +44(0)794 123 3917

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Eye Dam. 1: H318; Aquatic Acute 1: H400; Skin Sens. 1: H317

Most important adverse effects: May cause an allergic skin reaction. Causes serious eye damage. Very toxic to aquatic life.

2.2. Label elements

Label elements:

Hazard statements: H317: May cause an allergic skin reaction.

H318: Causes serious eye damage.

H400: Very toxic to aquatic life.

Signal words: Danger

Hazard pictograms: GHS05: Corrosion

GHS07: Exclamation mark

GHS09: Environmental



[cont...]

SAFETY DATA SHEET

WOODZONE MASONRY BIOCIDES

Page: 2

Precautionary statements: P101: If medical advice is needed, have product container or label at hand.
P102: Keep out of reach of children.
P272: Contaminated work clothing should not be allowed out of the workplace.
P273: Avoid release to the environment.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P302+352: IF ON SKIN: Wash with plenty of water/.
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310: Immediately call a.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

2-(2-BUTOXYETHOXY)ETHANOL

EINECS	CAS	PBT / WEL	CLP Classification	Percent
203-961-6	112-34-5	-	Eye Irrit. 2: H319	10-30%

3-LODO-2-PROPYNYL BUTYLCARBAMATE

259-627-5	55406-53-6	-	Acute Tox. 4: H302+332; Eye Dam. 1: H318; Aquatic Acute 1: H400; Skin Sens. 1: H317; STOT SE 3: H335	10-30%
-----------	------------	---	--	--------

SODIUMALKYL (C10-C14) BENZENESULPHONATE

-	85117-50-6	-	Acute Tox. 4: H302; Eye Dam. 1: H318; Skin Irrit. 2: H315	1-10%
---	------------	---	---	-------

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

[cont...]

SAFETY DATA SHEET

WOODZONE MASONRY BIOCIDES

Page: 3

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS. Refer to section 13 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

[cont...]

SAFETY DATA SHEET
WOODZONE MASONRY BIOCIDES

Page: 4

7.3. Specific end use(s)

Specific end use(s): No special requirement.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

2-(2-BUTOXYETHOXY)ETHANOL

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	67.5 mg/m ³	101.2 mg/m ³	-	-

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Respiratory protective device with particle filter.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Environmental: Refer to specific Member State legislation for requirements under Community environmental legislation.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Gold-brown

Odour: Characteristic odour

Evaporation rate: No data available.

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Soluble

Viscosity: Not applicable.

Boiling point/range°C: Not applicable.

Melting point/range°C: No data available.

Flammability limits %: lower: Not applicable.

upper: Not applicable.

Flash point°C: Not applicable.

Part.coeff. n-octanol/water: Not applicable.

Autoflammability°C: Not applicable.

Vapour pressure: Not applicable.

Relative density: Not applicable.

pH: Not applicable.

VOC g/l: Not applicable.

[cont...]

SAFETY DATA SHEET

WOODZONE MASONRY BIOCIDES

Page: 5

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.
Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

2-(2-BUTOXYETHOXY)ETHANOL

ORL	MUS	LD50	6050	mg/kg
ORL	RAT	LD50	4500	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Serious eye damage/irritation	OPT	Hazardous: calculated
Respiratory/skin sensitisation	DRM	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

[cont...]

SAFETY DATA SHEET
WOODZONE MASONRY BIOCIDES

Page: 6

Other information: Not applicable.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

3-LODO-2-PROPYNYL BUTYLCARBAMATE

BLUEGILL (<i>Lepomis macrochirus</i>)	96H LC50	0.23	mg/l
Daphnia magna	48H EC50	0.16	mg/l
GREEN ALGA (<i>Selenastrum capricornutum</i>)	72H ErC50	0.053	mg/l
RAINBOW TROUT (<i>Oncorhynchus mykiss</i>)	96H LC50	0.067	mg/l

12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Disposal of packaging: Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN3082

14.2. UN proper shipping name

Shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(3-LODO-2-PROPYNYL BUTYLCARBAMATE)

[cont...]

SAFETY DATA SHEET
WOODZONE MASONRY BIOCIDES

Page: 7

14.3. Transport hazard class(es)

Transport class: 9

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: Yes

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: E

Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: This product is a Seveso category/named substance in Annex I of Council Directive 96/82/EC.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

This safety data sheet is prepared in accordance with Commission Regulation (EC) No 1272/2008.

Phrases used in s.2 and s.3: H302: Harmful if swallowed.
H302+332: Harmful if swallowed or if inhaled.
H315: Causes skin irritation.
H317: May cause an allergic skin reaction.
H318: Causes serious eye damage.
H319: Causes serious eye irritation.
H335: May cause respiratory irritation.
H400: Very toxic to aquatic life.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.